

LEQ 55 SERIES OUTDOOR TAPS [LEQ55G-CB-x]

Cable Products, Mainline Passives

TaiTin

Description

TaiTin's LEQ 55 series taps have been designed with the future of the CATV industry in mind. All units come complete with a factory installed power passing bar for uninterrupted service when the faceplate is removed. Interchangeable faceplates allow for future network growth, while minimizing costly equipment upgrades for cable providers. All taps are backed by TaiTin's 1 year limited warranty.

Features

- 5–1002 MHz Bandwidth
- 12 A Current Capacity
- Aluminum Alloy Housing used for Corrosion Resistance
- Weather Rubber Gasket and RFI Shielding Mesh
- Double Polyurethane Coating for Greater Weather Protection
- Aerial or Pedestal Installation
- Printed Circuit Boards
- Equalizer Values of 7, 8, 9, 10 dB
- CB: Continuous through signal w/o faceplate
- Rotational Seizure Mechanism for Aerial or Pedestal Installation
- Compliant with SCTE guidelines



Ordering Information

LEQ55G - CB - X
 |
 |
 | 7, 8, 9, or 10 dB

Model Number	Inner Box	Standard Carton	Carton Weight	dB Values Available
LEQ55G-CB-x	10 pcs	40 pcs	17 kg / 38 lb	7, 8, 9, 10

Frequency	5-42	54-100	400	500	600	700	800	900	1002	MHz
Insertion Loss LEQ55G-CB-7	0.7	7.0	6.2	5.4	4.6	3.8	3.0	2.3	1.5	dB
Insertion Loss LEQ55G-CB-8	0.7	8.0	7.0	6.0	5.1	4.2	3.2	2.3	1.3	dB
Insertion Loss LEQ55G-CB-9	0.7	9.0	7.8	6.7	5.6	4.5	3.4	2.3	1.1	dB
Insertion Loss LEQ55G-CB-10	0.7	10.0	8.75	7.5	6.25	5.0	3.75	2.5	1.0	dB
Linear Equalization Slope					±0.7					
Return Loss Input/Output	15	16	18	18	17	16	16	16	16	dB