

# GALVANIC ISOLATORS [GxG-x]

Cable Products, Drop Passives

# TaiTin

## Description

TaiTin's galvanic isolator series are used to separate the subscriber's network equipment from the CATV network system as well as protect the network equipments from electrical hazards (i.e. voltage surges or lightning).

It is an effective and practical solution to prevent various types of hazardous surges from damaging Customer Premise Equipments (CPE).

## Features

- Class A - CENELEC EN50083-2 (Screening Effectiveness)
- EN/IEC 60728-11:2010 (Safety Requirements)
- 5-1002 MHz Bandwidth
- 1-, 2-, and 3-Port Splitter Design (1-Port Tubular Design Available)
- Protection for Subscriber's Premise Network Equipment Against Power Surges and Variabilities in Local Currents
- Superior Isolation and Return Loss for Return Path
- 2 kV DC Double Isolation Protection
- Standard Contact Pins
- Compact Design with Zinc Alloy Die-cast Housing & Tin Plated Soldered Back
- Two Ground Screws (Available)
- CE & RoHS Compliant



## General Specifications

|                        |                              |
|------------------------|------------------------------|
| Voltage Isolation:     | 2 kV DC                      |
| F Connector:           | SCTE Compliant IPS-SP 400    |
| Operation Temperature: | -40 to 60 °C (-40 to 140 °F) |
| RFI Shielding:         | -120 dB                      |

## Ordering Information

G **x** G - **x**

T for Tubular Housing (Leave Blank for Standard Housing)

1-, 2-, or 3-Port

| Model Number | Inner Box | Standard Carton | Carton Weight  |
|--------------|-----------|-----------------|----------------|
| G1G          | 10 pcs    | 300 pcs         | 20 kg / 44 lbs |
| G2G          | 10 pcs    | 300 pcs         | 21 kg / 46 lbs |
| G3G          | 10 pcs    | 300 pcs         | 22 kg / 48 lbs |
| G1G-T        | 10 pcs    | 300 pcs         | 20 kg / 44 lbs |



|           |              | G1G<br>One Port |     | G2G<br>Two Port |     | G3G<br>Three Port |     |     |     | G1G-T<br>One Port |     |    |
|-----------|--------------|-----------------|-----|-----------------|-----|-------------------|-----|-----|-----|-------------------|-----|----|
|           |              | Typ             | Max | Typ             | Max | Typ               | Max | Typ | Max | Typ               | Max |    |
| Frequency | 5-10 MHz     | 0.1             | 0.6 | 3.3             | 3.7 | 3.2               | 3.7 | 6.8 | 6.9 | 0.1               | 0.6 | dB |
|           | 11-40 MHz    | 0.1             | 0.4 | 3.3             | 3.9 | 3.3               | 3.9 | 6.6 | 6.9 | 0.1               | 0.4 | dB |
|           | 41-470 MHz   | 0.2             | 0.4 | 3.3             | 3.9 | 3.3               | 3.9 | 6.8 | 7.0 | 0.2               | 0.4 | dB |
|           | 471-862 MHz  | 0.4             | 0.7 | 4.0             | 4.3 | 3.9               | 4.3 | 7.0 | 7.5 | 0.4               | 0.7 | dB |
|           | 863-1002 MHz | 0.4             | 0.7 | 4.3             | 4.4 | 4.2               | 4.4 | 7.8 | 8.0 | 0.4               | 0.7 | dB |

|  |              | Min       | Typ | Min | Typ | Min | Typ | Min | Typ |    |
|--|--------------|-----------|-----|-----|-----|-----|-----|-----|-----|----|
|  |              | Frequency |     |     |     |     |     |     |     |    |
|  | 5-10 MHz     | 18        | 18  | 18  | 18  | 18  | 18  | 18  | 18  | dB |
|  | 11-470 MHz   | 18        | 20  | 18  | 20  | 18  | 20  | 18  | 20  | dB |
|  | 471-862 MHz  | 18        | 20  | 18  | 20  | 18  | 20  | 18  | 20  | dB |
|  | 863-1002 MHz | 18        | 20  | 18  | 20  | 18  | 20  | 18  | 20  | dB |

|  |              | Typ       | Min | Typ | Min | Typ | Typ |    |
|--|--------------|-----------|-----|-----|-----|-----|-----|----|
|  |              | Frequency |     |     |     |     |     |    |
|  | 5-10 MHz     | x         | 20  | 25  | 20  | 25  | x   | dB |
|  | 11-470 MHz   | x         | 20  | 25  | 20  | 25  | x   | dB |
|  | 471-862 MHz  | x         | 22  | 25  | 22  | 25  | x   | dB |
|  | 863-1002 MHz | x         | 20  | 22  | 20  | 22  | x   | dB |

|  |              | Typ       | Typ | Typ | Typ |    |
|--|--------------|-----------|-----|-----|-----|----|
|  |              | Frequency |     |     |     |    |
|  | 5-10 MHz     | 85        | 85  | 85  | 85  | dB |
|  | 10-12 MHz    | 85        | 85  | 85  | 85  | dB |
|  | 12-300 MHz   | 85        | 85  | 85  | 85  | dB |
|  | 301-470 MHz  | 80        | 80  | 80  | 80  | dB |
|  | 471-1002 MHz | 75        | 75  | 75  | 75  | dB |

|  |                  | Max  | Max  | Max  | Max  |    |
|--|------------------|------|------|------|------|----|
|  |                  |      |      |      |      |    |
|  | After 25 V Surge | -120 | -110 | -110 | -120 | dB |
|  | After 1 kV Surge | -120 | -110 | -110 | -120 | dB |

|  |   | Max        |  |
|--|---|------------|--|
|  |   |            |  |
|  | 2120 VDC*** Inner Conductor (Input Port) to Inner Conductor (Output Port) | 0.7 mA RMS |  |
|  | 2120 VDC*** Outer Conductor (Input Port) to Outer Conductor (Output Port) | 0.7 mA RMS |  |
|  | 230 VAC**** Inner Conductor (Input Port) to Inner Conductor (Output Port) | 2.0 mA RMS |  |
|  | 230 VAC**** Outer Conductor (Input Port) to Outer Conductor (Output Port) | 2.0 mA RMS |  |

- Notes:**
- \* 5-30 MHz (Transfer Impedance Method According EN-60728-2)
  - 30-1002 MHz (Absorption Clamp Method According EN-60728-2 Sec 4.4)
  - Two carriers (60 & 65 MHz), Output to Input, @ 120dBuV, before surge
  - \*\* Two carriers (60 & 65 MHz), Output to Input, @ 120 dBuV, after 10 pulses (25 V/1.2 uS rise time/500 uS fall time) at all ports
  - Two carriers (60 & 65 MHz), Output to Input, @ 120 dBuV, after 1 pulse (1 KV/1.2 uS rise time/500 uS fall time) at all ports
  - \*\*\* EN-60728-11/10 Safety Requirements: 2120 VDC ≥ 1 minute, I = ≤ 0.7 mA
  - \*\*\*\* EN-60728-11/10 Safety Requirements: 230 VAC, I = ≤ 2.0 mA (0 to 25 °C)