

Features

- Supports AC-coupled and DC-coupled Inputs
- Supports 8-bit, 10-bit and 12-bit Deep Color/Channel
- Transfers Bit Rates Up to 2.25 Gbps Channel
- Optimized Equalization for Enhanced Signal Integrity
- IR Controlled or Manual Switching
- Senses the Input Source Ports Automatically and Bypasses the Port Without a Signal
- CEC Pass By
- HDCP Compliant

Ordering Information

HDSW-**x** 1

3 or 5 input ports

Electrical Specifications

- 3 x 1 or 5 x 1 HDMI Switch
- Resolution: 1080p/1080i/720p/576p/480p/576i/480i
- Deep Color up to 36-bit
- Transfer Bitrates up to 2.25 Gbps/Channel
- Audio Formats; LPCM, Dolby-AC3, DTS7.1, DSD/Dolby True HD/DTS-HD Master Audio

General Specifications

HDMI Output Cable Distance (If a Longer Cable is Required, an Amplifier is Needed)	≤ 15 m
Operating Temperature Range	-5 to 55 °C (23 to 131 °F)
Operating Humidity Range	5 to 90% (No Condensation)
Product Dimensions (L x W x H)	117 x 63.5 x 23 mm (4.6 x 2.5 x 0.9 in.)

Package Includes

- 1x HDSW-x1
- 1x IR Remote Control
- 1x 5 V Universal Power Supply
- 1x User Manual

