

OPTICAL RECEIVER [OR4x-x]

Fiber Products, Receivers


TaiTin

Features

- Headend 19 in. Rack Mount Enclosure
- Supports 4 Optical Receiver Modules
- LED Status Monitor Indicators for Each Module
- RF Test Point Provided on Back Panel
- RF Output Level can be Adjusted
- Adjustable Attenuator Located on Front Panel
- Power of 135 ~ 250 VAC
- Weight of 3kg / 7lbs
- Dimensions (LxWxH) of 483. x 385 x 44 mm (19 x 15 x 1.75 in.)



Ordering Information



Model Number	Description	Box Weight
OR4x-x	Optical Receiver	3 kg / 7 lb

Optical Features

Output Wavelength	1200 ~ 1600 nm
Optical Input Range	-22 ~ 0 dBm
Optic Connector Type	Std: SC/APC or Option: FC/APC

RF Features

RF Bandwidth	5 ~ 200 MHz
Adjustable Output Level Attenuation	0 ~ -20 dB
Connector Type	"F" type

**Standard Warranty: Three Years

© Copyright 2012 TaiTin Enterprise Co., Ltd.. All rights reserved. This document is for information only. Features and specifications are subject to change without notice. v101413

TaiTin

FI 4-1 No: 31-1 Lane 169 KangNing Street, Xizhi District, New Taipei City, Taiwan 221 // Office: 886-2-2695-7348 // Fax: 886-2-2695-1931

Email: taitin.co@msa.hinet.net // www.taitin.com.tw